



Woodline® Renovator

Brand Cleaner and Reconditioner



DESCRIPTION:

Bona® Woodline® Renovator brand cleaner and reconditioner is recommended for cleaning and renovating wood floors that have been maintained with wax or penetrating stain.

FEATURES:

BEFORE USING, READ ALL DIRECTIONS AND MATERIAL SAFETY DATA SHEET #10020 FOR THIS PRODUCT.

Use directly from the can, do not thin.

Non-photochemically reactive (not an ozone precursor).

Apply Bona® Woodline® Renovator to an area not over 10 square feet. Immediately wipe or buff with a Bona® Conditioning Pad to remove old wax or penetrating stain. Change pads as needed. Wipe excess with clean towels. Allow to dry (approximately 30 minutes) before applying Bona® Woodline® DS-Stain or Luster Coat.

Coverage: Approximately 1,200 square feet per gallon.

Ingredients: Stoddard Solvent, Ethylene Glycol Monobutyl Ether, Aromatic Hydrocarbon Solvent, Diacetone Alcohol.

OSHA Class II (Combustible Liquid). Flash point: 110° F.

Storage and Disposal: Keep container closed when not in use. Do not transfer contents to other containers for storage and disposal. Do not return used material to original container; reapply or dispose of. In case of spillage, absorb with inert material. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

DANGER: RAGS, STEEL WOOL OR WASTE SOAKED WITH BONA® WOODLINE® RENOVATOR MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED, WATER-FILLED METAL CONTAINER.

PACKAGING:

- 1-gallon can

BonaKemi USA, Inc.

14805 E. Moncrieff Place, Aurora, CO 80011-1207 • (303) 371-1411 • FAX (303) 371-6958 • (800) 872-5515 • www.bonakemi.com
Item #1690 © 03/02 BonaKemi USA, Inc.