



## Product information

# SYNTEKO NEWSHINE 1696

### GENERAL DESCRIPTION

Synteko Newshine 1696 is a waterborne, practically odourless maintenance product which both renews the shine and protects finished wood floors, especially in high-traffic areas. It can be applied several times without a thick layer gradually building up.

### TECHNICAL DATA

<b>Base material</b>	Waterborne acrylic dispersion
<b>Solids content</b>	Approx. 11%
<b>Density</b>	Approx. 1100 kg/m <sup>3</sup> (9,18 lb/gal US) (11,02 lb/gal UK)
<b>pH</b>	Approx. 7
<b>Coverage</b>	Approx. 50 m <sup>2</sup> / l
<b>Drying time</b>	Approx. 30 minutes
<b>Gloss</b>	Approx. 50 (measured at 60°)
<b>Application</b>	Moist floor mop, non-flocculent cloth
<b>Shelf life</b>	36 months in unopened packing
<b>Storage</b>	Store frost free. Must be stored between +5°C (+40°F) and +30°C (+86°F)
<b>Cleaning</b>	Clean tools with water immediately after use

### DIRECTIONS FOR USE

Before applying Synteko Newshine make sure that the floor is clean. Sweep, mop or vacuum clean the floor. Old soaps, grease, polish etc. are removed by washing with water and Synteko Remover 1692 (see separate data sheet).

Apply Synteko Newshine in a thin, even layer using a moist floor mop or a non-flocculent cloth. Leave the floor to dry for approx. 30 minutes before walking on it. Synteko Newshine leaves a protective film, which will help maintain a beautiful look of the floor for longer time.

Subsequent treatment or polishing is not necessary. Cleaning can take place with a moist floor mop without Synteko Newshine 1696 being dissolved. Vacuum clean and mopping with a Synteko Super Clean 1697 solution and a well wrung cloth is normally sufficient.

## HEALTH & SAFETY INFORMATION

Keep out of reach of children. Detailed information and guidance is provided in our MSDS (Material Safety Data Sheet).



Akzo Nobel Decorative Coatings AB  
Synteko Floor Finishes  
SE-205 17 Malmö, Sweden  
Phone: +46 40 355000  
www.synteko.com  
Email: info@synteko.com



*Our information is based on laboratory tests and is considered a guide in connection with choice of product and working method. As your working conditions are beyond our control, we do not assume any responsibility for the results. Our responsibility covers exclusively personal injury and damage to property, which actually have been proved subsequent to faults and defects in one of the products manufactured by us.*

Date: 2004-04-15