



Product information

SYNTEKO RE-COVER 1620

DESCRIPTION

Synteko Re-Cover is an oxygen curing, faintly smelling oil for periodic maintenance of hardwood and cork floors treated with Synteko Belle 1614 or Synteko Solid 1612.

TECHNICAL DATA

Base material	Alkyd ester
Solids content	Approx. 77%
Solvent	Aromatic free white spirit (UK) / mineral spirit (USA)
Density	Approx. 910 kg/m ³ (7,59 lb/gal US) (9,12 lb/gal UK)
Fire hazards	Flammable. Flash point +40°C (104°F)
Coverage	* 50-100 m ² /l
Tools	For application: Rubber spatula or non-flocculent floor cloth For polishing: non-flocculent floor cloth
Cleaning	Clean tools with white spirit (UK)/mineral spirits (USA). See Safety below.

* Depending on tools and wood species.

DIRECTIONS FOR USE

Clean the floor with a Synteko Remover 1692 solution (see separate Product Information). Make sure that the floor is completely dry before applying Synteko Re-Cover.

Apply Synteko Re-Cover thin, with a rubber spatula, floor cloth or similar. Allow the floor to absorb Synteko Re-Cover for 10-15 min., and repeat application if necessary. Let the surface dry for 20 min and polish the floor with a clean, dry, non-flocculent floor cloth. The floor may be used after 2 to 4 hours.

The maintenance frequency will depend on traffic and how often the floor is cleaned. Normally, the frequency is every second year for residential areas, and approx. 2-4 times/year for commercial areas.

Regular maintenance will restore the lustre of the floor and keep it looking beautiful. Be sure to start regular maintenance before wearing through to bare wood.

HEALTH & SAFETY INFORMATION

Detailed information and guidance is provided in our MSDS (Material Safety Data Sheet). The following only represents a selection of important information.

Note: Flammable. Contains drying oil. Risk of self ignition. Collect and keep spillages, used rags etc in fireproof container and destruct. Keep out of reach of children.



Akzo Nobel Decorative Coatings AB
Synteko Floor Finishes
SE-205 17 Malmö, Sweden
Phone: +46 40 355000
www.synteko.com
Email: info@synteko.com



Our information is based on laboratory tests and is considered a guide in connection with choice of product and working method. As your working conditions are beyond our control, we do not assume any responsibility for the results. Our responsibility covers exclusively personal injury and damage to property, which actually have been proved subsequent to faults and defects in one of the products manufactured by us.

Date: 2004-04-15