



Product information

SYNTEKO HARDENER 1647

GENERAL DESCRIPTION

Synteko Hardener 1647 is a crosslinker intended for use only in combination with Synteko Classic 1636, 1637, 1646, a fast drying, two-component, acid-curing finish for hardwood floors in residential and commercial areas.

Note: Synteko Hardener must be mixed with Synteko Classic (see mixing instructions below and please read separate Product Information for Synteko Classic 1636, 1637, 1646).

TECHNICAL DATA

| | |
|-----------------------|---|
| Base material | p-Toluene sulphonic acid in ethanol and propylene glycol monomethyl ether |
| Solids content | Approx. 18% |
| Density | Approx. 900 kg/m ³ (7,51 lb/gal US) (9,02 lb/gal UK) |
| Shelf life | 24 months in tightly closed packing |
| Storage | Not sensitive to freezing |

MIXING AND POT-LIFE

Add 1 part of Synteko Hardener 1647 to 10 parts of Synteko Classic. Stir well to mix the hardener and the finish. The mixture can be used for 8 hours provided it is stored in a closed container.

HEALTH & SAFETY INFORMATION

Detailed information and guidance is provided in our MSDS (Material Safety Data Sheet). The following only represents a selection of important information.

Note: Highly flammable. Keep away from sources of ignition - No smoking. Do not empty into drains. Take precautionary measures against static discharges. Do not breath vapour or spray mist. Keep out of reach from children. If swallowed, seek medical advice immediately.



Akzo Nobel Decorative Coatings AB
Synteko Floor Finishes
SE-205 17 Malmö, Sweden
Phone: +46 40 355000
www.synteko.com
Email: info@synteko.com



Our information is based on laboratory tests and is considered a guide in connection with choice of product and working method. As your working conditions are beyond our control, we do not assume any responsibility for the results. Our responsibility covers exclusively personal injury and damage to property, which actually have been proved subsequent to faults and defects in one of the products manufactured by us.

Date: 2004-04-07